

Leland Limited Inc.
Product: Helium
Revised on:May 29,2018

1. Identification

Product Identifiner : Helium

Other means of : Helium, Helium gas, He, UN 1046

identification

Product use : Synthetic, Analytical chemistry

Supplier : Leland Limited, Inc.

2614 South Clinton Ave. South Plainfield, NJ 07080 1-908-668-1008 (9-5 EST)

Emergency calls

Hazmat Service Inc. : 1-800-373-7542 (Domestic)
Contract #1264 : 1-484-951-2432 (International)

2. Hazards Identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910. 1200).

: Gases under pressure - Compressed gas

Classification of the substance or mixture GHS label elements Hazard pictograms

substance or mixture



Signal word : Warning

Hazards statements : Contains gas under pressure; may explode if heated

May displace oxygen and cause rapid suffocation

May increase respiration and heart rate

Precautionary statements

General : Read and follow all Safety Data Sheets (SDS'S) before use. Read label

before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Close valve after each use and when empty. Use equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use a back flow preventative device in the piping. Use only equipment of compatible materials of construction. Always keep container in upright position.

Prevention : Use and store outdoors or in a well ventilated place.

Response : IF INHALED: Remove person to fresh air and keep comfortable for

breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Storage : Protect from sunlight. Protect from sunlight when ambient temperature

exceeds 40C/104F. Store in a well-ventilated place.

Disposal : Dispose in accordance with all applicable regulations.

Hazards not otherwise : In addition to any other important health or physical hazards, this product

classified may displace oxygen and cause rapid suffocation.



Leland Limited Inc. Product: Helium Revised on:May 29,2018

3. Composition, Information on Ingredients

Substance/Mixture : Substance Chemical Name : Helium

Synonyms : Helium, Helium gas, He, UN 1046

CAS Number : 7440-59-7 Content (vo%) : 99.5 % or more

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

4. First Aid Measures

Description of necessary first aid measures

Inhalation : Remove exposed person to fresh air and keep at rest in a position

comfortable for breathing. If not breathing, if breathing is irregular, or if respiratory arrest occurs, provide artificial respiration or oxygen by trained

personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen

tight clothing such as a collar, tie, belt or waistband.

Skin Contact : Helium is harmless at atmospheric pressure.

Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash

clothing before reuse. Clean shoes thoroughly before reuse.

Eye Contact : Helium is harmless at atmospheric pressure.

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

Ingestion : Since this product is a gas, refer to the inhalation section.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Inhalation : No known significant effects or critical hazards.

Skin Contact : Contact with rapidly expanding gas may cause burns or frostbite.

Eye Contact : Contact with rapidly expanding gas may cause burns or frostbite.

Frostbite : Try to warm up the frozen tissues and seek medical attention.

Ingestion : As this product is a gas, refer to the inhalation section.

Over-exposure signs/symptoms

Inhalation : No specific data.
Skin Contact : No specific data.
Eye Contact : No specific data.
Ingestion : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary



Leland Limited Inc. Product: Helium Revised on:May 29,2018

: Treat symptomatically. Contact poison treatment specialist immediately if Notes to physician

large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable

training. It may be dangerous to the person providing aid to give

mouth-to-mouth resuscitation.

5. Fire Fighting Measures

Extinguishing media

Suitable extinguishing

media

Unsuitable extinguishing

media

Specific hazards arising from the chemical

Hazardous thermal

decomposition products Special protective actions

for fire-fighters

Use an extinguishing agent suitable for the surrounding fire.

: None known.

: No specific data.

: Contains gas under pressure. In a fire or if heated, a pressure increase

will occur and the container may burst or explode.

: Promptly isolate the scene by removing all persons from the vicinity of the

incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Contact supplier immediately for specialist advice. Move containers from fire area if this can be done without risk.

Use water spray to keep fire-exposed containers cool.

Special protective

equipment for fire-fighters

Fire-fighters should wear appropriate equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive

pressure mode.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

For non-emergency

personnel

: No action shall be taken involving any personal risk or without suitable

adequate ventilation. Wear appropriate respirator when ventilation is

training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Avoid breathing gas. Provide

inadequate. Put on appropriate personal protective equipment.

If specialized clothing is required to deal with the spillage, take note of any For emergency responders

information in Section 8 on suitable and unsuitable materials. See also

the information in "For non-emergency personnel".

Environmental precautions : Ensure emergency procedures to deal with accidental gas releases are in

> place to avoid contamination of the environment. Inform the relevant authorities if the product has caused environmental pollution (sewers,

waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill : Immediately contact emergency personnel. Stop leak if without risk.

Large spill Immediately contact emergency personnel. Stop leak if without risk. Note:

see Section 1 for emergency contact information and Section 13 for

waste disposal.



Leland Limited Inc. Product: Helium Revised on:May 29,2018

7. Handling and Storage

Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8).

> Contains gas under pressure. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Empty containers retain product residue and can be hazardous. Do not puncture or incinerate container. Use equipment rated for cylinder pressure. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. Use a

suitable hand truck for cylinder movement.

Advice on general occupational hygiene Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also

Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep container tightly closed and sealed until ready for use. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Cylinder temperatures

should not exceed 40C (104F).

8. Exposure Controls and Personal Protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Helium	Oxygen Depletion [Asphyxiant]

Appropriate engineering

controls

: Good general ventilation should be sufficient to control worker exposure to

airborne contaminants.

Environmental exposure control

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce

emissions to acceptable levels.

Individual protection measures

Hygiene measures Wash hands, forearms and face thoroughly after handling chemical

products, before eating, smoking, using the lavatory and at the end of your

shift.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the

workstation location.

: Safety eyewear complying with an approved standard should be used Eye/Face protection

when a risk assessment indicates this is necessary to avoid exposure to



Leland Limited Inc.
Product: Helium
Revised on:May 29,2018

liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved

standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances,

the protection time of the gloves cannot be accurately estimated.

Body protection : Personal protective equipment for the body should be selected based on

the task being performed and the risks involved and should be approved

by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should

be selected based on the task being performed and the risks involved and

should be approved by a specialist before handling this product.

Respiratory protection : Use a properly fitted, air-purifying or air-fed respirator complying with an

approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the

selected respirator.

9. Physical and Chemical Properties

Appearance

Physical state : Gas [Compressed gas]

Color : Colorless

Molecular weight : 4 g/mol

Molecular formula : He

Boiling/condensation point -268.9C (-452F)

Melting/freezing point : -272.2C (-458F)

Critical temperature : -267.9C (-450.2F)

Odor : Odorless
Odor threshold : Not available.
pH : Not available.

Flash point : [Product does not sustain combustion.]

Burning time : Not applicable.

Burning rate : Not applicable.

Evaporation rate : Not available.

Flammability (solid, gas) : Not available.

Lower and upper explosive : Not available.

(flammable) limits

Vapor pressure : Not available

Vapor density : 0.14 (Air = 1), Liquid Density@BP: 7.8 lb/ft³ (125 kg/m³)

Specific Volume : 96.1538 ft³/lb



Leland Limited Inc.
Product: Helium
Revised on:May 29,2018

Gas Density : 0.0104 lb/ft³
Relative density : Not applicable.
Solubility : Not available.
Solubility in Water : Not available.

Partition coefficient: : 0.28

n-octanol/water

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

SADT : Not available.

Viscosity : Not applicable.

10. Stability and Reactivity

Reactivity : No specific test data related to reactivity is available for this product or its

ingredients.

Chemical stability : The product is stable.

Possibility of hazardous : Under normal conditions of storage and use, hazardous reactions will not

reactions occur.

Conditions to avoid : No specific data.

Hazardous decomposition : Under normal conditions of storage and use, hazardous decomposition

products should not be produced.

Hazardous polymerization : Under normal conditions of storage and use, hazardous polymerization

will not occur.

11. Toxicological Information

Information on toxicological effects

Acute toxicity : Not available. Irritation / Corrosion : Not available. Not available. Sensitization : Not available. Mutagenicity : Not available. Carcinogenicity Reproductive toxicity : Not available. Not available. **Teratogenicity** Specific target organ toxicity: Not available.

(single exposure)

Specific target organ toxicity: Not available.

(repeated exposure)

Aspiration hazard : Not available. Information on the likely : Not available.

routes of exposure

Potential acute health effects

Eye contact : Contact with rapidly expanding gas may cause burns or frostbite.

Inhalation : No known significant effects or critical hazards.

Skin contact : Contact with rapidly expanding gas may cause burns or frostbite.

Ingestion : Since this product is a gas, refer to the inhalation section.



Leland Limited Inc. Product: Helium Revised on:May 29,2018

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.
Inhalation : No specific data.
Skin contact : No specific data.
ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available. Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available. Potential delayed effects : Not available.

Potential chronic health effects - Not available.

General : No known significant effects or critical hazards.
Carcinogenicity : No known significant effects or critical hazards.
Mutagenicity : No known significant effects or critical hazards.
Teratogenicity : No known significant effects or critical hazards.
Developmental effects : No known significant effects or critical hazards.
Fertility effects : No known significant effects or critical hazards.
No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates : Not available.

12. Ecological Information

Toxicity : Not available. Persistence and : Not available.

degradability

Bioaccumulative potential

Product/Ingredient name	Log P _{ow}	BCF	Potential
Helium	0.28	-	low

Mobility is soil

Soil/Water partition : Not available.

coefficient (K_{OC})

Other adverse effects : No known significant effects or critical hazards.



Leland Limited Inc. Product: Helium Revised on:May 29,2018

13. Disposal Considerations

Discharge of Helium Gradually release in open air.

Disposal of Cylinders : If gas remains in cylinders, release gas with proper equipment and

dispose of cylinders as incombustible waste.

For empty cylinders, check for a puncture hole and dispose of as

incombustible waste.

Do not dispose of cylinders without first checking that all gas has been

released.

14. Transport Information

DOT / IMDG : Helium, Compressed

Shipping Name

UN Number : UN 1046 Hazard Class (Division) : 2 (2.2)

Placard (When required) : Nonflammable gas

NON-FLAMMABLE GAS

Special Shipping : See CFR 49, 172.101, 173.306 for exceptions of labeling.

Information

IMDG / IMO : Receptacles, small containing gas (Gas Cartridge < 50ml)

Proper Shipping Name

UN Number : UN 2037 Hazard Class (Division) : 2 (2.2)

Special Provision : See Code 191

IATA : Receptacles, small containing gas

Proper Shipping Name

UN Number : UN2037 Hazard Class (Division) : 2 (2.2)

Special Provision : See Code A98

15. Regulatory Information

The following selected regulatory requirements may apply to this product. Not all such requirements are identified. Users of this product are solely responsible for compliance with all applicable federal, state, and local regulations.

U.S. Federal Regulations : None of this products components are listed under SARA Sections

302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process

safety plan.

SARA 311/312 : Fire hazard : No Hazardous Categories : Sudden release of pressure : Yes



Leland Limited Inc.
Product: Helium
Revised on:May 29,2018

Reactive : No Immediate (acute) health hazard : No Delayed (chronic) health hazard : No

State Regulations : Massachusetts : This material is listed.

New York : This material is not listed.
New Jersey : This material is listed.
Pennsylvania : This material is listed.
California : This material is not listed.

International Regulations : Canada inventory This material is listed or exempted.

Australia inventory (AICS) This material is listed or exempted. China inventory (IECSC) This material is listed or exempted.

Japan inventory Not determined.

Korea inventory This material is listed or exempted.

Malaysia inventory Not determined.

(EHS Register)

New Zealand inventory of This material is listed or exempted.

Chemicals (NZIoC)

Philippines inventory This material is listed or exempted.

(PICCS)

Taiwan inventory (CSNN) Not determined.

16. Other Information

Hazard Rating Systems : NFPA Ratings HMIS Ratings

Health = 0Health = 0Flammability = 0Flammability = 0Reactivity = 0Physical hazards = 0

Special = SA

Key to abbreviations

ACGIH : American Conference of Governmental Industrial Hygienists

BCF : Bioconcentration Factor CAS : Chemical Abstract Services

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act

CFR : United States Code of Federal Regulations

DOT : Department of Transportation

GHS : Globally Harmonized System of Classification and Labeling of Chemicals

IATA
 International Air Transport Association
 IMDG
 International Maritime Dangerous Goods
 IMO
 International Maritime Organization

Log P_{ow} : Logarithm of the octanol/water partition coefficient

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

STEL : Short-term Exposure Limit

SARA : Superfund Amendments and Reauthorization Act

TLV : Threshold Limit Value

TSCA : Toxic Substances Control Act
TWA : Time Weighted Average



Leland Limited Inc.
Product: Helium
Revised on:May 29,2018

Notice to reader:

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee they are the only hazards that exist.